




CATALOG 2024

AIRPORT FRANGIBLE CAMERA POLE



Airport Weather Observation System Towers and Camera poles are in Compliance for Full Impact Testing with ICAO guidelines Aerodrome Design Manual Part-6, chapter 5 and US Department of Transportation, FAA Advisory Circular No 150/5345-45C, April 2007

SGS FRANGIBLE TOWERS PRIVATE LIMITED


SAFE & STRONG

DATA SHEET

Equipment: Airport Camera

Frangible Pole

Pole Model: PT 9060 - Camera



DESCRIPTION- ACCESSORIES

Pole Mast:	Length (options)	2.0 - 4.5 meter
	Material	Composite Fiberglass
	Colour	Option I- Aviation Yellow
		Option II- Aviation
		Red & white
		PU 2 part paint, UV protected
Camera	Universal mounting	Suitable for all instruments
Mounting:	Special Mounting	Tailor made mounting available
	Camera Unit	In customer scope
Enclosure (Optional):	UV protected IP65 Enclosure, make FIBOX Germany with mounting kit	
Lighting Arrester Kit (Optional):	75 cm Copper rod with spool, 50 sq. mm 5 meter Copper Earthing wire, Connecting thimbles, 2 meter ground copper rod/strip. (not included in layout)	
Base Plate:	Aluminum Casted Base	
Foundation Bolts:	Galvanized Bolts and nuts	
Warranty:	3 years on complete tower Change in any colour warranted for 5 years	

CERTIFICATION

Third party full crash test certificate as per compliance for full impact testing with ICAO guidelines Aerodrome design manual Part-6, chapter 5 and US department of transportation, FAA Advisory circular No 150/5345, April 2007













COMPLIANCE

- Compliance with FAA AC 150/5345-45C and Compliance with ICAO guidelines Aerodrome Design Material Part-6 Frangibility Doc 9157 First Edition – 2006 chapter 5.
- Wind load deflection test
- Salt Spray Test as per MIL-STD-810F & ISO 9227: 2017
- Temperature Resistance Test -40°C to +65°C
- Flammability Test IS: 6746 1994

- Di-Electric Strength Test: ASTM D 149:2009.
- UV Resistance Test ASTM G 154: 2016/IS-14887
- Tensile Strength Test: ASTM D638
- Flexural Strength Test: ASTM D790
- Flame Spread & Smoke develop Index test ASTM E84



SGS FRANGIBLE TOWERS PRIVATE LIMITED

- 36, Udyog Vihar, Phase IV, Gurgaon 122015, Haryana, INDIA
- Tel: +91-124-4810917, 4810918, 4810919, 4810920, Fax: +91-124-4000184
- www.sgsfrangible.com, sales@sgsfrangible.com